MicroSpeed Power Module









ERNI's 2.0 mm pitch MicroSpeed Power Module excellent EMC shielding adds up to 18A per contact and stacks 5 - 20 mm. This 5 pin solution has excellent retention force, blind mating is available and offers SMT, THR & SMT/THR termination styles.

Click here or scan the QR code to launch the MicroSpeed video

or type this URL into your browser >>> https://rebrand.ly/ERNI-MicroSpeed-Video-E





POWER IS ITS ELEMENT. MICROSPEED POWER MODULE IS SMALL ON SPACE AND BIG ON POWER.

- high signal integrity
- EMC improved shielding (high interference-resistance / excellent EMC)
- high current density
- blind-mate variants available
- automatic process capable
- stack heights from 5 to 20 mm
- current rating up to 18A
- pronounced pre-alignment
- reliable retention force on the PCB

Pitch	2.0mm
No. of Pins	5
Termination	SMT, SMT/THR
Current rating (A)	up to 18A per contact
Temperature range	-55 °C to 125 °C
Board-to-Board Height	5 - 20 mm

APPLICATIONS (not limited to)

Automation - PLC, DC, Remote I/O,
Drives
Medical
Aerospace
Military
Automotive

For more information on MicroSpeed Power Moduleor any ERNI connectors, please contact your ERNI Sales Manager or 1-804-228-4100 to speak an ERNI connector specialist.