3.2" Front Light Panel

12936-01 | Product Data Sheet | 2020



Overview

The **FLEx Front Light Panel** optical film is designed to laminate to the front surface of **Sharp reflective display (LS032B7DD02)** to provide high quality on-demand display lighting. This thin plastic panel incorporates only a single LED which enables product designers to develop ultra-thin devices and minimize battery use.

- One low-power LED (included in Front Light)
- Over 80x less power compared to traditional backlighting
- 0.05 mm thick FLEx film is over **5x thinner** than alternative lightguides
- Simple I/F and Connectivity to System Board

For more information:


WEB flexlighting.com

CONTACT flexlighting.com/contact

PHONE 773-295-0305




Mechanical



Flexible film allows for different placement options for the light source (examples below)

All dimensions in mm

PRELIMINARY



3.2" Front Light Panel

12936-01 | Product Data Sheet | 2020



Electrical

Item	Symbol	Typical	Absolute Max	Unit
Forward Current	l _F	60	80	mA
Pulse Forward Current	l _{EP}		200	mA
Reverse Voltage	V	2.95	3.4	V

For more information:


WEB flexlighting.com

CONTACT flexlighting.com/contact

PHONE 773-295-0305


Example ZIF Connectors:


- Molex 503480-0400
- Molex 52745-0497
- Molex 54550-0471
- Molex 54548-0471 (bottom)
- Molex 505110-0492




Optical (PRELIMINARY)

3.2" Sharp + Front Light (12936-01)							
Item		Symbol	TYP.	Unit	Remark		
Viewing Angle CR >2	V	Θ 11 Θ 12		° (Degree)	· [Remark 1]		
	Н	Θ 21 Θ 22		° (Degree)			
Contrast Ratio	Front light ON	CR	9		[Remark 2]		







Remark 2: Definition of Contrast Ratio

Contrast Ratio (CR) = Reflection intensity in white display
Reflection intensity in black display

Measurements taken with a Minolta Chroma Meter CS-100 at a 17" view distance